CONFIDENTIAL

May 1, 1957

Balloon, Jower d

25X1

DOO S REV DATE	1/2/0 BY 3537	2
CAIG COMP OS OPE CAIG CLASS S PAGES	5 G TYPE O/	
JUST NEXT RE	V 2016 AUTH: HR	15-2

The following describes tentative requirements or desired operational characteristics of powered lighter-than-air vehicles as it is now planned they be utilized. They must be regarded as tentative and are considered at this time only as a possible aid in the emphasis on certain areas of the general research effort. It is desired that these characteristics be discussed fully at this time and at such time as all parties concerned with this effort are in agreement the desired characteristics will be set forth in final form and may serve as one of the major considerations in directing the remainder of the effort.

Two general operating characteristics are envisioned at this time that will probably result in two types of lighter-than-air vehicles. One, a very high altitude, long "range" vehicle capable of extended flight duration. Number two is a a minimum size, caomparatively high speed, "low" altitude vehicle.

No. I - "High altitude: long range"

	Minimum Useful	Desired	Probable Max.
Payload (lbs)	100	500-400	1000
Time at alt. without power (de		7 - 10	30 🔨
Cruising range (mi) - power or	110	400 - 700	44
Sea level max speed (knots)	25 40K	45 - 55 50-80	**
Other requirements for #I:	Minimum optical and Capable of unmanned (directed remotely thirds of the cru tude, power on an Minimum ground faci (space, personnel	directed fli over approx- ising range) d off heading lity for laun	ght two- alti- ching

No. II - High speed, low altitude, short range

Payload (lbs.)	Minimum Useful 400	Desired 200 - 700	Probable Max. 1000
Cruising altitude	7,000	7 - 10,000	15,000
Time at alt. Sher off (hours)	FRIENDAL &	* · · · · · · · · · · · · · · · · · · ·	

*				
livia ()	M	nimum Usefal	Desired	Probable Max.
Cruising range - power on (mi)		100	100-500	derende
Maximum speed at sea level		30	50 - 80	2040040
Other requirements for #II:	(1)	The vehicle v	rill be manual	ly operated
	(2) Very high degree of stability and control (must maneuver close to the ground, while the payload is decreased by as much as two thirds			
		Must be able to operate completely during the hours of darkness		mpletely during
	(4)	Minimum redar	r target	
	(5)	Minimum "audi	o" target	
	•	risual problem itudes during		-

These outline in general terms the tentative operating characteristics. It is recognized that this subject has not been exhausted and it is planned that final type requirements will be set forth at a later date pending agreement by all concerned.

Stu

imt

